

Tryark FR Coverall

ARKFR220C

DESCRIPTION

TIL Workwear Try Ark Flame Retardant (FR) Coverall are carefully constructed with premium materials that meets or exceed safety standards and are designed for maximum comfort, durability and protection against hazardous conditions. Our 100% cotton fabrics provide the wearer with maximum comfort. Naturally soft, these fabrics offer an excellent moisture management control and are engineered to sustain extensive industrial launderings.

KEY FEATURES

- 100% Cotton
- Flame Resistant

DETAILED FEATURES

- Premium flame retardant fabric
- Reinforced stitching for durability
- Multiple pockets for storage
- Comfortable fit for ease of movement
- Durable and long-lasting materials
- Easy to clean and maintain

APPLICATIONS

- Oil & Gas Industry
- Manufacturing
- Construction
- Mining
- Logistics
- Warehousing

 **Royal Blue** Code: RYB



OTHER COLORS



Sunrise Orange **Navy Blue** **Tan Brown** **Ribbon Red** **Ocean Blue**

PRODUCT INFORMATION

Category: Workwear
Available Sizes: 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60

PACKAGING WASTE

Material	Type	Unit	Weight (g)	Length (mm)	Width (mm)	Height (mm)
Cardboard	Outer	1	0.05	0.716	0.232	0.414
Plastic	Inner	1	0.01	0.5	0.4	0.0
Paper	Inner	1	0.002	0.21	0.148	0.0




Tryark FR Coverall

ARKFR220C

Technical Data		
Parameter	Specification	Standard / Test Method
Product Code	ARKFR220C	
Width	148 cm (+2/-1 cm)	ISO 22198:2006
Weight	220g/m ² (±5%)	ISO 3801:1977
Composition	100% Cotton	
Construction	Twill 3/1 S	
Available finishes	Durable flame-retardant finish	

Physical Performance		
Parameter	Specification	Standard / Test Method
Tensile Strength	1000 N x 450 N (± 10%)	NEN-EN-ISO 13934-1: 2013
Tear Strength	25 N x 25 N (± 10%)	NEN-EN-ISO 13937-2: 2000
pH	4 - 7.5	NEN-EN-ISO 3071: 2005

Flammability Performance		
Parameter	Specification	Standard / Test Method
After Wash and Dry	50 Cycles	ISO 15797 procedure 8, 75 C: 2002
Ignition to surface	Meets ISO 14116: 2015 index 3	ISO 15025 Part A: 2000

Care Labelling		
Parameter	Specification	Standard / Test Method
Domestic Laundering	    	
Industrial Laundering	75°C	
PPE Requirements	 optional: 	

Certifications		
Icon	Specification	Standard / Test Method
	Industrial flame and heat hazards	EN ISO 11612:2008 A1, B1, C1, F1 (A1 + A2= 100 x ISO 15797 - 75°C)
	Contrast colours: Delftblue 89249, Twilight 89250	EN ISO 20471: 2013
	General requirements***	EN ISO 13688: 2013
	Öko-Tex Standard 100, class 2	Centexbel, no. 0903009



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. PARKER Coverall declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.

