

Midrian Inherent FR Ecogreen Detachable Female Coverall

MIDFRD200C

DESCRIPTION

Midrian Inherent FR Ecogreen Detachable Female Coverall - 200g/m² (Modacrylic/Lyocell/Para-Aramid/Static-Control). Specially designed for field working women, providing excellent protection in harsh environments with comfort-focused design.

KEY FEATURES

- Designed for women
- Detachable
- Ecogreen
- Flame Resistant
- High Visibility
- Washable

DETAILED FEATURES

- Detachable design for versatility
- 200g/m² Modacrylic/Lyocell/Para-Aramid/Static-Control fabric
- Turn Down Collar design
- Front Closure with Flame Retardant Metal Zipper and Snap Buttons
- 2 Chest Pockets Closed with FR Metal Zipper
- 2 Back Pockets with FR Snap Buttons
- Stitched with FR Threads ensuring durability
- Bar Tack at all Stress Points adding strength
- Elastic Waistband adding flexibility and comfort
- Cuffs with Snap Closures
- 50mm FR Reflective Tape on Shoulders, Sleeves, and Legs
- 2 Side Swing Pockets with Fabric and Inner Access Openings
- Hanging Loops
- 1 Ruler Pocket on Trousers
- 1 Sleeve Pocket with Flap and Velcro Closure

APPLICATIONS

- Oil & Gas Industry
- Petrochemical work
- Electrical utilities
- Welding operations
- Flash fire hazard areas
- Electric arc environments
- Field operations



Ocean Blue Code: OCB



OTHER COLORS



Sunrise
Orange

Navy Blue

Tan Brown

Ribbon Red

Royal Blue

Green

PRODUCT INFORMATION

Category: Workwear

Available Sizes: 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58

PACKAGING WASTE

Material	Type	Unit	Weight (g)	Length (mm)	Width (mm)	Height (mm)
Cardboard	Outer	1	0.05	0.716	0.232	0.414
Plastic	Inner	1	0.01	0.5	0.4	0.0
Paper	Inner	1	0.002	0.21	0.148	0.0



Midrian Inherent FR Ecogreen Detachable Female Coverall

MIDFRD200C

Technical Data

Parameter	Specification	Standard / Test Method
Product Code	MIDFRD200C	
Width	150 cm (+2/-1 cm)	ISO 3801:1978
Weight	200g/m ² (±5%)	ISO 3932:1980
Composition	Modacrylic/lyocell/para-aramid/Static-Control™	
Construction	2/1 twill	
Available finishes	Standard: Comfort. Optional: Hydro-Tec	

Physical Performance

Parameter	Specification	Standard / Test Method
Tensile Strength	700 N x 500 N (± 10%)	ISO 13934-1:1999
Tear Strength	40 N x 30 N (± 10%)	NEN-EN-ISO 13937-1:2000

Care Labelling

Parameter	Specification	Standard / Test Method
Domestic Laundering	    	
Industrial Laundering	70°C	
PPE Requirements	   optional:  	

Certifications

Icon	Specification	Standard / Test Method
	Industrial flame and heat hazards	EN ISO 11611, 11612 A1, A2, B1, C1, E1, F1: 2015 (A1 + A2 = 100 x ISO 15797 - 75°C)
	Short-duration thermal exposures from fire	NFPA 2112: 2018
	Electric Arc	Single Layer: EN IEC 61482-1-2, class 1; 2015 HRC/Category 1 (4 ≤ ATPV ≥ 8 cal/cm ²) System: XL9200 + XL9240 EN IEC 61482-1-2; 2015 class 2 (7kA) System: HRC/Category 2 (8 ≤ ATPV ≥ 25 cal/cm ²)
	Anti-Static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals **	EN 13034: 2005 + A1: 2009
	Contrast colours: Delftblue 89249, Twilight 89250	EN ISO 20471: 2013
	General requirements**	EN ISO 13688: 2013
	Öko-Tex Standard 100, class 2	Centexbel, no. 0903009



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. PARKER Coverall declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.

